

Compact Shaker KS 15 A control



Description

The programmable Orbital Shaker KS 15 A control with digital display for reproducible shaking tasks. The loading capacity is 15 kg on a shaking platform of 400 x 300 mm.

Basic Equipment

Basic device without shaking plate, **without rack system**
With digital display and programmable control.

Loading Capacity

| | |
|---------------------------|-----------|
| Erlenmeyer flasks 100 ml | 20 pieces |
| Erlenmeyer flasks 250 ml | 12 pieces |
| Erlenmeyer flasks 500 ml | 6 pieces |
| Erlenmeyer flasks 1000 ml | 4 pieces |
| Separating funnels 250 ml | 1 pieces |

You will find further loading possibilities [here](#)

Option:

[Control interface](#)

[USB interface](#)

Details

Motion: orbital
Shaking platform: 400 x 300 mm
Max. load: 15 kg
Shaking speed: 30 - 420 rpm, in steps of 5
Stroke: 17 mm
Runtime: programmable / continuous
Order No.: 6170 000
Accessory: Rack System Combifix KS
Universal tray KS
Incubator Hood TH 15

Technical specifications

Electrical supply: 230 V or 115 V, 50 / 60 H please indicate in case of order
Enclosure protection: IP 21
Heat emission: approx. 10 - 15 W
Ambient temperature: 5°C to 50°C
Relative humidity: ~ 85 %
Dimensions (w x d x h): 510 x 490 x 150 mm
Weight: 19 kg